


□□□□ CSCA 45□□□□□□□□


□□	CSPCD 55 100□□□□□□□□□□□□□□
□□□□	4□6 C□
□□□□□□	□□
□□	□□□□
□□□□	□
□□	□□ □□□□□□□□
□□□□	3.2m□□□□□□□□
□□	45gsm□□□□□□□□□□40-200gsm□
□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□	□□□□□□□□□□□□□□□□□□□□□□□□

□□□□ CSCA 45□□□□□□□□

A close-up photograph showing the edge of a nonwoven fabric. The fabric is light-colored with a fine, fibrous texture. A diagonal line separates the smooth, white surface of the fabric from the rougher, greyish edge. Two website URLs are overlaid on the image.


www.nonwovenproductsulipper.com

www.guidenonwoven.com



www.nonwovenproductsulipper.com

www.guidenonwoven.com



www.nonwovenproductsulipper.com

www.guidenonwoven.com

□□□□□□CSCA 45□□□□□□



Packed in rolls,
with 2 " or 3 "
core inside,
strong poly
bags outside



transporting the goods
to the port



loaded in container

CSCA 45

Q	A
Q1	A1
Q2	A2 1; 1ton
Q3	A3
Q4	A4
Q5	A5
Q6	A6 2-4
Q7	A7 OEM

