JL-2025[illegible]

[illegible]	JL-2025[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	[illegible]
[illegible]	3.2M[illegible]
[illegible]	[illegible] [illegible]150℃[illegible]
[illegible]	[illegible] [illegible][illegible]

JL-2025[illegible]

www.nonwovenproductsulipper.com
www.guidenonwoven.com

www.nonwovenproductsulipper.com
www.guidenonwoven.com

JL-2025□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□



JL-2025□□□□□□□□□□□□□□□□□□□□□□

□	□□
□□□□□□□□	A1□□□□□□□
□□2□□□□□□□□□□□□	A2□□□□1□
□□3□□□□□□□□□□□	A3□□
□□4□□□□□□□□□□□	A4□□□□□□□□□□□□
Q5□□□□□□□□□□□□□□□□□□□□□□	A5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
Q6□□□□□□□□□□□	A6□□□□□□□□□□□□□□□□□□□□□□□□□□□2-4□□□□□□□□□□□□□□
Q7□□□□□□□□□□□□□□	A7□□□□□□□□□OEM□□□□□□□□□□□□□
□8□□□□□□□□□□□□□	A8□□□□□□□□□□□□□□□□24□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□