


WH1 45 gsm SMS

WH1 45 gsm SMS	
	WH1
	3.2M
	<ul style="list-style-type: none"> <li>-</li> <li>-</li> <li>-</li> <li>-</li> </ul>

	GSM	45.04	ASTM D3776
MD	N /5	109.43	ASTM D5035-95
CD	N /5	54.43	ASTM D5035-95
MD		113.07	ASTM D5035-95
CD		85.83	ASTM D5035-95
	2Ø	53	IST 80.6
	L / <sup>2</sup> -S	195.99	ASTM D737-75

WH1 45 gsm SMS



[www.nonwovenproductsulipper.com](http://www.nonwovenproductsulipper.com)

[www.guidenonwoven.com](http://www.guidenonwoven.com)



[www.nonwovenproductsulipper.com](http://www.nonwovenproductsulipper.com)

[www.guidenonwoven.com](http://www.guidenonwoven.com)


□□□□□□□□WH1□□45□□□□□□□□SMS□□□



Packed in rolls,  
with 2 " or 3 "  
core inside,  
strong poly  
bags outside



loaded in container



transporting the goods  
to the port

**WH1**

Q	A1
Q2	A2
Q3	A3
Q4	A4
Q5	A5
Q6	A6
Q7	A7
Q8	A8

